



Mark on the cap and the glass shell

—Trade Mark : NP

--Year of the manufacture (on the glass shell)

Combind M&E Strength, lbs 22000

Creepage distance (in) 12.625

Tension Proof lbs 11000

Low Frequency Flashover Dry, kV 80

Low Frequency Flashover Wet, kV 50

Critical Impulse Flashover Pos, kV 125

Critical Impulse Flashover Neg, kV 130

Low Frequency Puncture, kV 130

Radio Influence voltage data Test Voltage, RMS to ground, kV 10

Radio Influence voltage data Max RIV at 1000kHz,  $\mu V$  50

Approx nct weight (kg) 3.6

Test standard: ANSI

7	SU-2	Cushion	1	Low density polythene									
6	T8	Glass part	1	Toughened glass									
5	J2-5-1	Pin	1	Forged steel coating	Marker	Revise	Rename	Signature	Date	52-3H w/Zinc Sleeve		NEWELL-PSN LLC	
4	Y-2	Cushion	1	Asphalt felt	Design			Date					
3		Cement	1	Aluminous Cement	Mapping			Date					
2	R16	Cotter pin	1	Stainless steel	Technics			Date					
1	52-3	Cap	1	Malleable cast iron	Auditing			Date		Weight	Scale	Drawing NO. G523-7001	
Index	Code	Name	QTY	Description	Assessment			Date		3.6 (kg)	1:1.5		