


MECHANICAL CHARACTERISTICS  
 CANTILEVER STRENGTH, LBS 8000  
 TENSILE STRENGTH, LBS 28000  
 TORSIONAL STRENGTH, IN-LBS 40000  
 COMPRESSION STRENGTH, LBS 40000  
 ELECTRICAL CHARACTERISTICS  
 POS. CRITICAL F.O., kV 125  
 IMPULSE WITHSTAND, kV 110  
 60 HZ WET WITHSTAND, kV 45  
 RIV CHARACTERISTICS  
 60 HZ TEST VOLTAGE, kV 10  
 MAX. RIV AT 1000 KHz, v V 50  
 PHYSICAL CHARACTERISTICS  
 LEAKAGE DISTANCE, IN 15.5  
 COLOR: GRAY  
 TESTED PER ANSI C29.1 (LATEST REVISION)  
 & ANSI C 29.9 (LATEST REVISION)

$\frac{5}{8}$ " - 11UFS-2B  
 4 HOLES AT 90° ON 5.00" B.C.,  
 $\frac{5}{8}$ " DEEP BOTH ENDS



AB

					110kV -BIL NON-STACKING STATION POST		DRAWING 4 1012-7001	
					TR-235		PHASE SIGN	WEIGHT SCALE
					MATERIAL PORCELAIN		TOTAL 1 PAGES	PAGE 1
					NEWELL-PSN LLC			
SIGN	QTY	REJIGGER #	NAME	DATE				
DRAWN								
CHECKED								
APPROVE								
DATE								