



Technical Specification

- | | |
|--|---------------------|
| 1.Connection Type | B&S Type K |
| 2.Leakage Distance | 11 inches (279mm) |
| 3.M&E Strength, | 40000 lbs (178kN) |
| 4.Tension Proof. | 20000 lbs(89kN) |
| 5.Impact Strength, | 90 inch-lbs (10N-m) |
| 6.Low-Frequency Dry Flashover Voltage | 80kV |
| 7.Low-Frequency Wet Flashover Voltage | 50kV |
| 8.Critical Impulse Flashover Voltage, Positive | 125kV |
| 9.Critical Impulse Flashover Voltage, Negative | 130kV |
| 10.Low-Frequency Puncture Voltage | 110kV |
| 11.Radio-Influence Voltage: | |
| Low-Frequency Test Voltage | 10kV |
| Maximum RIV at 1,000 kHz | 50 µV |
| 12.Color | Per Order |
| 13.All Tolerances are According to ANSI C29.2B Unless Specified Otherwise. | |

7	Corrosion Sleeve	1	Zinc	
6	Split pin	1	Stainless steel	
5	Cushion	1	Asphalt	
4	Cement		Portland	
3	Pin	1	Forged steel,hot dip galvanized	
2	Cap	1	Malleable cast iron,hot dip galvanized	
1	Porcelain	1	C130	
Item	Title/Name	Quantity	Note	
Designed by		Porcelain Disc Insulator Light Gray	Cat/Art	52-8H
Checked by			Dwg.No.	232528Z-7001
Approved by			Issue	1
Date	2019.5.14		NEWELL-PSN LLC	
Weight	17.5lbs			