


RELEASE HISTORY

a	DRAWING/DESIGN CREATED Rev.0	20.12.2014 SNR
b	DRAWING REDRAWN Rev.1	10.04.2021 RVS



 In.(mm)	PART# 41650-7001
	DRAWING NUMBER 3CY2.807.136
TITLE N-NECK VERTICAL TIE-TOP LINE POST INSULATOR	

REF. ANSI TECHNICAL REFERENCE # 57-4



**TECHNICAL CHARACTERISTICS**

**MECHANICAL RATINGS**

CANTILEVER STRENGTH, lbs (kN) 2800 (12.5)

**ELECTRICAL RATINGS**

CRITICAL IMPULSE FLASHOVER VOLTAGE, POSITIVE, kV 255  
 LOW FREQUENCY FLASHOVER VOLTAGE, DRY, kV 150  
 LOW FREQUENCY FLASHOVER VOLTAGE, WET, kV 125

**RADIO INFLUENCE VOLTAGE RATINGS**

LOW FREQUENCY TEST VOLTAGE, kV 44  
 MAX. RIV AT 1000 kHz, μV 200

**PHYSICAL CHARACTERISTICS**

MINIMUM LEAKAGE DISTANCE, in (mm) 40 (1016)  
 DRY ARCING DISTANCE, in (mm) 14.5 (368)  
 NET WEIGHT, lbs (kg) 39 (17.7)  
 GLAZE COLOR Light Gray

APPLICABLE STANDARD : ANSI : C29.7

VISUAL AND DIMENSIONAL INSPECTION ACCORDING TO IEC 383

MATERIAL	PORCELAIN	REF.	DWG.TYPE SALES	DWN. RVS	APP.
----------	-----------	------	----------------	----------	------